

KUMO VI



The power package for demanding digital signage

Digital-Signage-PC with Nvidia RTX 3060

The KUMO VI is equipped with an Intel® Core i5-11400H processor and an Nvidia RTX 3060. This Mini-PC is the perfect companion for demanding Digital Signage applications. Also the areas of Virtual Reality, Artificial Intelligence and Machine Learning are a no brainer for the KUMO VI.

Technical Data

General

CPU	Intel® Core i5-11400H
Applications	Digital Signage, Multi monitor
Power consumption Idle in W	44
Ambient conditions	0°C up to +35°C
Cooling	active

Power supply

DC In	19,5V / 17A
Input voltage PSU	100 - 240V

Connectors

Video output	HDMI 2.1, DisplayPort 1.4a
HDMI 2.1	2
DisplayPort 1.4a	2
Audio output	1x Line-Out, 1x Mic-In
Thunderbolt 4	1
Gigabit LAN	1
2.5 Gigabit LAN	1
USB 3.1 Gen 2	5
2,5" drive	1
SD card	SD/SDHC/SDXC card

Dimensions

Height	61 mm
Width	208 mm
Depth	204 mm
Wall mount	yes

Graphics

Dedicated graphics	Nvidia RTX 3060
VRAM	6 GB GDDR6
Independent displays	4
Video resolution	7690x4320 @ 60Hz (8K)

Other

OS	Windows 11 Professional, Windows 10 IoT Enterprise 2021 LTSC Value
Warning Class A	The device is intended for use in an industrial environment. The operation of this device can cause radio interference in residential areas.
Warning of use 802.11a	If you want to use the WLAN module according to 802.11a in the 5 GHz range: Use in the frequency range 5150 MHz - 5350 MHz is only permitted indoors!