

WINDBOX II Pro



With the flat design and high performance the WINDBOX II Pro can be used in the industrial field, in offices and also in the digital signage field.

Industrial PC for different applications

The characteristics of our WINDBOX II Pro are definitely its flat design and high performance. Like that, the system can be used in the industrial field, in offices and also in the digital signage field.

Technical Data

General

CPU	Intel® Celeron J3455
Application	Digital Signage, Industrial PC, MSI IPC
Power consumption Idle in W	5
Ambient conditions	0°C up to +40°C
Cooling	passive

Power supply

DC In	19V / 3,42A
Input voltage PSU	100 - 240V

Connectors

Video output	DisplayPort, HDMI (no hot plug)
DisplayPort 1.2	2
HDMI 2.0	1
Gigabit-LAN	2
USB 2.0	1
USB 3.2	3
COM RS232	1
2,5" drive	1

Dimensions

Height	19 mm
Width	255 mm
Depth	180 mm
Wall mount	yes
VESA mount	75x75

Graphics

Integrated graphics	Intel® HD Graphics
Independent displays	3
Video resolution	4K @ 60 Hz

Other

OS	Windows 10 IoT Enterprise 2019 LTSC Entry
Warning Class A	The device is intended for use in an industrial environment. The operation of this device can cause radio interference in residential areas.
Warning of use 802.11a	If you want to use the WLAN module according to 802.11a in the 5 GHz range: Use in the frequency range 5150 MHz - 5350 MHz is only permitted indoors!