

spo-book NANO H110

Einstiegsmodell mit Desktop CPU // Intel® Skylake Desktop CPU

Entry-level system with Desktop CPU // Intel® Skylake Desktop CPU



Specification // Technische Daten

| | |
|------------------------|---|
| CPU | Intel® Core i7 6700T 4 x 2.8 GHz (max. 4 x 3.6 GHz), Intel® Core i5 6600T 4 x 2.7 GHz (max. 4 x 3.6 GHz), Intel® Core i3 6100T 2 x 3,2 GHz, Intel® G4400T 2 x 3,3 GHz |
| Chipset | Intel® H110 |
| RAM | max. 32768 MB SO-DDRIV RAM |
| GPU | Intel® HD Graphics 530 |
| Storage | 2,5" SATA III HDD or SSD // M.2 SATA SSD (2280) |
| ODD | no |
| Expansions | WiFi, BT |
| Dimensions (H x W x D) | 34 x 178 x 178 mm |
| Weight | ca. 1,5 kg |
| Power Consumption | Standby: < 1 Watt Idle: ca. 30 Watt Full Load: ca. 48 Watt |
| Power Source | externes Netzteil / external power adapter 220V auf 19V / 4,74 A |
| Cooling | aktive Kühlung / Smart Fan Solution |
| VESA / Wall Mount | yes / yes |
| Material | Metall / Metal |
| Availability | Langzeitverfügbarkeit / long term availability |
| Application | Digital Signage, Industrial Control, KIOSK / POS |
| Environment | 0° C - 40 ° C at 20%-85% rel. hum. |

| | |
|--------------|--|
| Frontpanel | 4 x USB 3.0 2 x Audio |
| Backpanel | 1 x COM (1 x COM RS232) 4 x USB 2.0 1 x Realtek® Gigabit LAN 1 x VGA 1 x HDMI 1 x DP 2 x Antenne |
| Certificates | CE, CB |
| Website |  |